

**Type : IS-IS/C430M**  
**Function : Double Incoming Cubicle with LBS**  
**W x D x H : 500 x 850 x 1610 mm**  
**Weight : 250 kg**

**Standard Equipment :**

- 2 Set of busbar 630 A , made of CU
- 2 Motorized operated rotary load break switch ISR SF6 630 A
- 2 Motorized control type tumbler C430M
- 2 Earthing switch of the quick closing type
- 6 Voltage dividers and 6 neon lamps for indication of live cables
- 2 Mechanical Interlocking system by construction
- Provision for mounting 1 or 3 core cable connections

**Accessories Equipment :**

- 2 Heating resistor 220 Vac, 50 W
- 2 Aux. Relay c/w Socket for Control
- Push Button & Pilot Lamp for Status Indicating
- 2 MCB 2P, 6A for Control Circuit Protection
- 1 Automatic Transfer Relay for DDBC

|             |              |                      |   |   |   |        |
|-------------|--------------|----------------------|---|---|---|--------|
|             | First Issued | Modification Project |   |   | <b>SW ENGINEERING</b>                   |        |
|             |              | A                    | B | C |   |        |
| Dated       | 14-Feb-08    |                      |   |   | Project Name :<br><br><b>ATS System</b> | Page : |
| Issued by   | WH           |                      |   |   |   | 2 of 2 |
| Checked by  | WH           |                      |   |   |   |        |
| Approved by | YB           |                      |   |   |   |        |